




## *HiFi Audio Codec*

### Application Programming Interface (API) Definition

For Xtensa HiFi Audio Engines



Cadence Design Systems, Inc.  
2655 Seely Ave.  
San Jose, CA 95134  
[www.cadence.com](http://www.cadence.com)

© 2016 Cadence Design Systems, Inc.  
All Rights Reserved

This publication is provided "AS IS." Cadence Design Systems, Inc. (hereafter "Cadence") does not make any warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Information in this document is provided solely to enable system and software developers to use our processors. Unless specifically set forth herein, there are no express or implied patent, copyright or any other intellectual property rights or licenses granted hereunder to design or fabricate Cadence integrated circuits or integrated circuits based on the information in this document. Cadence does not warrant that the contents of this publication, whether individually or as one or more groups, meets your requirements or that the publication is error-free. This publication could include technical inaccuracies or typographical errors. Changes may be made to the information herein, and these changes may be incorporated in new editions of this publication.

© 2016 Cadence, the Cadence logo, Allegro, Assura, Broadband Spice, CDNLIVE!, Celtic, Chipestimate.com, Conformal, Connections, Denali, Diva, Dracula, Encounter, Flashpoint, FLIX, First Encounter, Incisive, Incyte, InstallScape, NanoRoute, NC-Verilog, OrCAD, OSKit, Palladium, PowerForward, PowerSI, PSpice, Purespec, Puresuite, Quickcycles, SignalStorm, Sigrity, SKILL, SoC Encounter, SourceLink, Spectre, Specman, Specman-Elite, SpeedBridge, Stars & Strikes, Tensilica, TripleCheck, TurboXim, Vectra, Virtuoso, VoltageStorm, Xplorer, Xtensa, and Xtreme are either trademarks or registered trademarks of Cadence Design Systems, Inc. in the United States and/or other jurisdictions.

OSCI, SystemC, Open SystemC, Open SystemC Initiative, and SystemC Initiative are registered trademarks of Open SystemC Initiative, Inc. in the United States and other countries and are used with permission. All other trademarks are the property of their respective holders.

Version 1.0

May 2016

PD-16-8559-10-00

## Contents

---

1.	Introduction to the HiFi Audio Codec API .....	1
1.1	Document Overview .....	1
2.	Generic HiFi Audio Codec API.....	2
2.1	Memory Management.....	3
2.1.1	API Object.....	3
2.1.2	API Memory Table .....	3
2.1.3	Persistent Memory.....	3
2.1.4	Scratch Memory.....	3
2.1.5	Input Buffer .....	3
2.1.6	Output Buffer .....	4
2.2	C Language API .....	4
2.3	Generic API Errors.....	5
2.4	Commands .....	6
2.4.1	Start-up API Stage.....	7
2.4.2	Set Codec-Specific Parameters Stage .....	7
2.4.3	Memory Allocation Stage.....	8
2.4.4	Initialize Codec Stage .....	9
2.4.5	Get Codec-Specific Parameters Stage.....	10
2.4.6	Execute Codec Stage .....	10
2.5	Files Describing the API .....	11
2.6	HiFi API Command Reference .....	11
2.6.1	Common API Errors.....	12
2.6.2	XA_API_CMD_GET_LIB_ID_STRINGS .....	13
2.6.3	XA_API_CMD_GET_API_SIZE.....	16
2.6.4	XA_API_CMD_INIT .....	17
2.6.5	XA_API_CMD_GET_MEMTABS_SIZE.....	21
2.6.6	XA_API_CMD_SET_MEMTABS_PTR.....	22
2.6.7	XA_API_CMD_GET_N_MEMTABS .....	23
2.6.8	XA_API_CMD_GET_MEM_INFO_SIZE .....	24
2.6.9	XA_API_CMD_GET_MEM_INFO_ALIGNMENT .....	25
2.6.10	XA_API_CMD_GET_MEM_INFO_TYPE .....	26
2.6.11	XA_API_CMD_GET_MEM_INFO_PRIORITY .....	27
2.6.12	XA_API_CMD_SET_MEM_PTR .....	29
2.6.13	XA_API_CMD_INPUT_OVER.....	31
2.6.14	XA_API_CMD_SET_INPUT_BYTES .....	32
2.6.15	XA_API_CMD_GET_CURIDX_INPUT_BUF .....	33
2.6.16	XA_API_CMD_EXECUTE .....	34

2.6.17	XA_API_CMD_GET_OUTPUT_BYTES.....	36
3.	HiFi Audio Codec API Specifics .....	37
3.1	Codec Specific Files .....	38
3.2	Codec Specific Error Codes .....	38
3.3	Configuration Parameters.....	38
3.3.1	XA_API_CMD_SET_CONFIG_PARAM .....	39
3.3.2	XA_API_CMD_GET_CONFIG_PARAM.....	40
3.3.3	Configuration Parameter Details .....	41
4.	References .....	42

## Figures

Figure 1 HiFi Audio Codec Interfaces .....	2
Figure 2 API Command Sequence Overview.....	6
Figure 3 Flow Chart for typical command sequence .....	37

## Tables

Table 2-1 Codec API .....	4
Table 2-2 Error Codes Format.....	5
Table 2-3 Commands for Initialization .....	7
Table 2-4 Commands for Setting Parameters.....	7
Table 2-5 Commands for Initial Table Allocation.....	8
Table 2-6 Commands for Memory Allocation .....	8
Table 2-7 Commands for Initialization .....	9
Table 2-8 Commands for Getting Parameters .....	10
Table 2-9 Commands for Codec Execution .....	10
Table 2-10 XA_CMD_TYPE_LIB_NAME subcommand .....	13
Table 2-11 XA_CMD_TYPE_LIB_VERSION subcommand .....	14
Table 2-12 XA_CMD_TYPE_API_VERSION subcommand .....	15
Table 2-13 XA_API_CMD_GET_API_SIZE command .....	16
Table 2-14 XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS subcommand.....	17
Table 2-15 XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS subcommand .....	18
Table 2-16 XA_CMD_TYPE_INIT_PROCESS subcommand.....	19
Table 2-17 XA_CMD_TYPE_INIT_DONE_QUERY subcommand .....	20
Table 2-18 XA_API_CMD_GET_MEMTABS_SIZE command .....	21
Table 2-19 XA_API_CMD_SET_MEMTABS_PTR command .....	22
Table 2-20 XA_API_CMD_GET_N_MEMTABS command.....	23
Table 2-21 XA_API_CMD_GET_MEM_INFO_SIZE command .....	24
Table 2-22 XA_API_CMD_GET_MEM_INFO_ALIGNMENT command.....	25
Table 2-23 XA_API_CMD_GET_MEM_INFO_TYPE command.....	26
Table 2-24 Memory Type Indices .....	26
Table 2-25 XA_API_CMD_GET_MEM_INFO_PRIORITY command .....	27
Table 2-26 Memory Priorities .....	28

Table 2-27 XA\_API\_CMD\_SET\_MEM\_PTR Command ..... 29

Table 2-28 XA\_API\_CMD\_INPUT\_OVER command ..... 31

Table 2-29 XA\_API\_CMD\_SET\_INPUT\_BYTES command..... 32

Table 2-30 XA\_API\_CMD\_GET\_CURIDX\_INPUT\_BUF command ..... 33

Table 2-31 XA\_CMD\_TYPE\_DO\_EXECUTE subcommand..... 34

Table 2-32 XA\_CMD\_TYPE\_DONE\_QUERY subcommand..... 35

Table 2-33 XA\_API\_CMD\_GET\_OUTPUT\_BYTES command ..... 36

Table 3-1 XA\_API\_CMD\_SET\_CONFIG\_PARAM..... 39

Table 3-2 XA\_API\_CMD\_GET\_CONFIG\_PARAM ..... 40

## Document Change History

---

Version	Changes
1.0	<ul style="list-style-type: none"> <li>• Initial version</li> </ul>

# 1. Introduction to the HiFi Audio Codec API

---

The HiFi Audio Codec Application Programming Interface (API) is a C-callable API that is exposed by all the HiFi based Audio Codecs developed by Cadence. An “audio codec” is a generic term for any audio processing component and is not restricted to encoders and decoders. The audio codec is created using the Xtensa® Software Development Toolkit [\[1\]](#) and is targeted to a specific HiFi core [\[2\]](#).

A light-weight version of the API called the “HiFi Speech Codec API” [\[3\]](#) is used for smaller components (for example, speech codecs) that do not require all the features of this API.

The API has gone through several revisions. This document covers the latest revision, that is, Revision 1.16.

## 1.1 Document Overview

The HiFi codec libraries implement a simple API to encapsulate the complexities of the coding operations and simplify the application and system implementation. Parts of the API are common to all the HiFi codecs, these are described in Section 2 after the introduction. Section 3 covers optional additional features that may be implemented by a particular HiFi codec.

## 2. Generic HiFi Audio Codec API

This section describes the API that is common to all the HiFi audio codec libraries. The API facilitates any codec that works in the overall method shown in the following diagram.




Figure 1 HiFi Audio Codec Interfaces

Section 2.1 discusses all the types of run time memory required by the codecs. There is no state information held in static memory, therefore a single thread can perform time division processing of multiple codecs. Additionally, multiple threads can perform concurrent codec processing. The API is implemented so that the application does not need to consider the codec implementation.

Through the API, the codec requests the minimum sizes required for the input and output buffers. Prior to executing the codec execution command, the codec requires that the input buffer be filled with data up to the minimum size for the input buffer. However, the codec may not consume all of the data in the input buffer. Therefore, the application must check the amount of input data consumed, copy downwards any unused portion of the input buffer, and then continue to fill the rest of the buffer with new data until the input buffer is again filled to the minimum size. The codec will produce data in the output buffer. The output data must be removed from the output buffer after the codec operation.

Applications that use these libraries should not make any assumptions about the size of the PCM “chunks” of data that each call to a codec produces or consumes. Although normally the chunks are the exact size of the underlying frame of the specified codec algorithm, they will vary between codecs and also between different operating modes of the same codec. The application should provide enough data to fill the input buffer. However, some codecs do provide information, after the initialization stage, to adjust the number of bytes of the input data they need.

## 2.1 Memory Management

The HiFi audio codec API supports a flexible memory scheme and a simple interface that eases the integration into the final application. The API allows the codecs to request the required memory for their operations during run time.

The run time memory requirement consists primarily of the scratch and persistent memory. The codecs also require an input buffer and output buffer for the passing of data into and out of the codec.

### 2.1.1 API Object

The codec API stores its data in a small structure that is passed via a handle that is a pointer to an opaque object from the application for each API call. All state information and the memory tables that the codec requires are referenced from this structure.

### 2.1.2 API Memory Table

During the memory allocation, the application is prompted to allocate memory for each of the following memory areas. The reference pointer to each memory area is stored in this memory table. The reference to the table is stored in the API object.

### 2.1.3 Persistent Memory

This is also known as static or context memory. This is the state or history information that is maintained from one codec invocation to the next within the same thread or instance. The codecs expect that the contents of the persistent memory be unchanged by the system apart from the codec library itself for the complete lifetime of the codec operation.

### 2.1.4 Scratch Memory

This is the temporary buffer used by the codec for processing. The contents of this memory region should be unchanged if the actual codec execution process is active, that is, if the thread running the codec is inside any API call. This region can be used freely by the system between successive calls to the codec.

### 2.1.5 Input Buffer

This is the buffer used by the algorithm for accepting input data. Before the call to the codec, the input buffer needs to be completely filled with input data.

## 2.1.6 Output Buffer

This is the buffer in which the algorithm writes the output. This buffer needs to be made available for the codec before its execution call. The output buffer pointer can be changed by the application between calls to the codec. This allows the codec to write directly to the required output area. The codec will never write more data than the requested size of the output buffer.

## 2.2 C Language API

A single interface function is used to access the codec, with the operation specified by command codes. The actual API C call is defined per codec library and is specified in the codec-specific section. Each library has a single C API call.

The C parameter definitions for every codec library are the same and are specified in the following table:

Table 2-1 Codec API

<b>xa_&lt;codec&gt;</b>	
Description	This C API is the only access function to the audio codec.
Syntax	<pre>XA_ERRORCODE xa_&lt;codec&gt;(     xa_codec_handle_t p_xa_module_obj,     WORD32 i_cmd,     WORD32 i_idx,     pVOID pv_value);</pre>
Parameters	<p>p_xa_module_obj Pointer to the opaque API structure</p> <p>i_cmd Command.</p> <p>i_idx Command subtype or index</p> <p>pv_value Pointer to the variable used to pass in, or get out properties from the state structure</p>
Returns	Error Code based on the success or failure of the API command

The types used for the C API call are defined in the supplied header files as:

```
typedef signed int      WORD32;
typedef void           *pVOID;
```

Each time the C API for the codec is called, a pointer to a private allocated data structure is passed as the first argument. This argument is treated as an opaque handle as there is no requirement by the application to look at the data within the structure. The size of the structure is supplied by a specific API command so that the application can allocate the required memory. Do not use `sizeof()` on the type of the opaque handle.

Some command codes are further divided into subcommands. The command and its subcommand are passed to the codec via the second and third arguments respectively.

When a value must be passed to a particular API command or an API command returns a value, the value expected or returned is passed through a pointer, which is given as the fourth argument to the C API function. In the case of passing a pointer value to the codec, the pointer is just cast to `pVOID`. It is incorrect to pass a pointer to a pointer in these cases. An example would be when the application is passing the codec a pointer to an allocated memory region.

Due to the similarities of the operations required to decode or encode audio streams, the HiFi Audio Engine API allows the application to use a common set of procedures for each stage. By maintaining a pointer to the single API function and passing the correct API object, the same code base can be used to implement the operations required for any of the supported codecs.

## 2.3 Generic API Errors

The error code returned is of type `XA_ERRORCODE`, which is of type `signed int`. The format of the error codes are defined in the following table.

Table 2-2 Error Codes Format

31	30-15	14 - 11	10 - 6	5 - 0
Fatal	Reserved	Class	Codec	Sub code

The errors that can be returned from the API are subdivided into those that are fatal, which require the restarting of the whole codec and those that are nonfatal and are provided for information to the application.

The class of an error can be API, Config, or Execution. The API errors are concerned with the incorrect use of the API. The Config errors are produced when the codec parameters are incorrect or outside the supported usage. The Execution errors are returned after a call to the main encoding or decoding process and indicate situations that have arisen due to the input data.

## 2.4 Commands

This section covers the commands associated with the following command sequence overview flow chart. For each stage of the flow chart there is a section that lists the required commands in the order they should occur. For individual commands, definitions, and examples refer to Section 2.6. The codecs have a common set of generic API commands that are represented by the white stages. The yellow stages are specific to each codec.




Figure 2 API Command Sequence Overview

## 2.4.1 Start-up API Stage

The following commands should be executed once each during start-up. The commands to get the various identification strings from the codec library are for information only and are optional. The command to get the API object size is mandatory as the real object type is hidden in the library and therefore there is no type available to use with `sizeof()`.

Table 2-3 Commands for Initialization

Command / Subcommand	Description
XA_API_CMD_GET_LIB_ID_STRINGS XA_CMD_TYPE_LIB_NAME	Get the name of the library.
XA_API_CMD_GET_LIB_ID_STRINGS XA_CMD_TYPE_LIB_VERSION	Get the version of the library.
XA_API_CMD_GET_LIB_ID_STRINGS XA_CMD_TYPE_API_VERSION	Get the version of the API.
XA_API_CMD_GET_API_SIZE	Get the size of the API structure.
XA_API_CMD_INIT XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS	Set the default values of all the configuration parameters.

## 2.4.2 Set Codec-Specific Parameters Stage

Refer to the specific codec section for the parameters that can be set. These parameters either control the decoding/encoding process or determine the output format of the decoder/encoder output data.

Table 2-4 Commands for Setting Parameters

Command / Subcommand	Description
XA_API_CMD_SET_CONFIG_PARAM XA_<codec>_CONFIG_PARAM_<param_name>	Set the codec-specific parameter. See the codec-specific section for parameter definitions.

### 2.4.3 Memory Allocation Stage

The following commands should be executed once only after all the codec-specific parameters have been set. The API is passed the pointer to the memory table structure (MEMTABS) after it is allocated by the application to the size specified. After the codec specific parameters are set, the initial codec setup is completed by performing the post-configuration portion of the initialization to determine the initial operating mode of the codec and assign sizes to the blocks of memory required for its operation. The application then requests a count of the number of memory blocks.

Table 2-5 Commands for Initial Table Allocation

Command / Subcommand	Description
XA_API_CMD_GET_MEMTABS_SIZE	Get the size of the memory structures to be allocated for the codec tables.
XA_API_CMD_SET_MEMTABS_PTR	Pass the memory structure pointer allocated for the tables.
XA_API_CMD_INIT XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS	Calculate the required sizes for all the memory blocks based on the codec-specific parameters.
XA_API_CMD_GET_N_MEMTABS	Obtain the number of memory blocks required by the codec.

The following commands should then be executed in a loop to allocate the memory. The application first requests all the attributes of the memory block and then allocates it. It is important to abide by the alignment requirements. Finally, the pointer to the allocated block of memory is passed back through the API. For the input and output buffers it is not necessary to assign the correct memory at this point. The input and output buffer locations must be assigned before their first use in the EXECUTE stage. The type field refers to the memory blocks, for example input or persistent, as described in Section 2.1.

Table 2-6 Commands for Memory Allocation

Command / Subcommand	Description
XA_API_CMD_GET_MEM_INFO_SIZE	Get the size of the memory type being referred to by the index.
XA_API_CMD_GET_MEM_INFO_ALIGNMENT	Get the alignment information of the memory-type being referred to by the index.
XA_API_CMD_GET_MEM_INFO_TYPE	Get the type of memory being referred to by the index.
XA_API_CMD_GET_MEM_INFO_PRIORITY	Get the allocation priority of memory being referred to by the index.
XA_API_CMD_SET_MEM_PTR	Set the pointer to the memory allocated for the referred index to the input value.

## 2.4.4 Initialize Codec Stage

The following commands should be executed in a loop during initialization. These commands should be called until the initialization is completed as indicated by the `XA_CMD_TYPE_INIT_DONE_QUERY` command. In general, decoders can loop multiple times until the header information is found. However, encoders will perform exactly one call before they signal they are done.

There is a major difference between encoding Pulse Code Modulated (PCM) data and decoding stream data. During the initialization of a decoder, the initialization task reads the input stream to discover the parameters of the encoding. However, for an encoder there is no header information in PCM data. Even so, the encoder application is still required to perform the initialization described in this stage. However, encoders will not consume data during initialization. Further, this has an implication in that some encoders provide parameters that can be used to modify the input buffer data requirements after the initialization stage. These modifications will always be a reduction in the size. The application only needs to provide the reduced amount per execution of the main codec process.

In general, the application will signal to the codec the number of bytes available in the input buffer and signal if it is the last iteration. It is not normal to hit the end of the data during initialization, but in the case of a decoder being presented with a corrupt stream it will allow a graceful termination. After the codec initialization is called, the application will ask for the number of bytes consumed. The application can also ask if the initialization is complete, it is advisable to always ask, even in the case of encoders that require only a single pass. A decoder application must keep iterating until it is complete.

Table 2-7 Commands for Initialization

Command / Subcommand	Description
<code>XA_API_CMD_SET_INPUT_BYTES</code>	Set the number of bytes available in the input buffer for initialization.
<code>XA_API_CMD_INPUT_OVER</code>	Signal to the codec the end of the bit stream.
<code>XA_API_CMD_INIT</code> <code>XA_CMD_TYPE_INIT_PROCESS</code>	Search for the valid header, does header decoding to get the parameters and initializes state and configuration structures.
<code>XA_API_CMD_INIT</code> <code>XA_CMD_TYPE_INIT_DONE_QUERY</code>	Check if the initialization process has completed.
<code>XA_API_CMD_GET_CURIDX_INPUT_BUF</code>	Get the number of input buffer bytes consumed by the last initialization.

## 2.4.5 Get Codec-Specific Parameters Stage

Finally, after the initialization, the codec can supply the application with information. In the case of decoders this would be the parameters it has extracted from the encoded header in the stream.

Table 2-8 Commands for Getting Parameters

Command / Subcommand	Description
XA_API_CMD_GET_CONFIG_PARAM XA_<codec>_CONFIG_PARAM_<param_name>	Get the value of the parameter from the codec. See the codec-specific section for parameter definitions.

## 2.4.6 Execute Codec Stage

The following commands should be executed continuously until the data is exhausted or the application wants to terminate the process. This is similar to the initialization stage, but includes support for the management of the output buffer. After each iteration, the application requests how much data is written to the output buffer. This amount is always limited by the size of the buffer requested during the memory block allocation. (To alter the output buffer position use XA\_API\_CMD\_SET\_MEM\_PTR with the output buffer index.)

Table 2-9 Commands for Codec Execution

Command / Subcommand	Description
XA_API_CMD_INPUT_OVER	Signal the end of bit stream to the library.
XA_API_CMD_SET_INPUT_BYTES	Set the number of bytes available in the input buffer for the execution.
XA_API_CMD_EXECUTE XA_CMD_TYPE_DO_EXECUTE	Execute the codec thread.
XA_API_CMD_EXECUTE XA_CMD_TYPE_DONE_QUERY	Check if the end of stream has been reached.
XA_API_CMD_GET_OUTPUT_BYTES	Get the number of bytes output by the codec in the last frame.
XA_API_CMD_GET_CURIDX_INPUT_BUF	Get the number of input buffer bytes consumed by the last call to the codec.

## 2.5 Files Describing the API

### The common include files (`include`)

- `xa_apicmd_standards.h`  
The command definitions for the generic API calls
- `xa_error_standards.h`  
The macros and definitions for all the generic errors
- `xa_memory_standards.h`  
The definitions for memory block allocation
- `xa_type_def.h`  
All the types required for the API calls

## 2.6 HiFi API Command Reference

In this section, the different commands are described along with their associated subcommands. The only commands missing are those specific to a particular codec. These commands are generally the SET and GET commands for the operational parameters.

The commands are listed below in sections based on their primary commands type (`i_cmd`). Each section contains a table for every subcommand. In the case of no subcommands the one primary command is presented.

The commands are followed by an example C call. Along with the call there is a definition of the variable types used. This is to avoid any confusion over the type of the 4th argument. The examples are not complete C code extracts as there is no initialization of the variables before they are used.

The errors returned by the API are detailed after each of the command definitions. However, there are a few errors that are common to all the API commands; these are listed in Section 2.6.1. All the errors possible from the codec-specific commands will be defined in the codec-specific sections. Further, the codec-specific sections also cover the Execution errors that occur during the initialization or execution calls to the API.

## 2.6.1 Common API Errors

These errors are fatal and should not be encountered during normal application operation. They signal that a serious error has occurred in the application that is calling the codec.

- **XA\_API\_FATAL\_MEM\_ALLOC**  
`p_xa_module_obj` is NULL
- **XA\_API\_FATAL\_MEM\_ALIGN**  
`p_xa_module_obj` is not aligned to 4 bytes
- **XA\_API\_FATAL\_INVALID\_CMD**  
`i_cmd` is not a valid command
- **XA\_API\_FATAL\_INVALID\_CMD\_TYPE**  
`i_idx` is invalid for the specified command (`i_cmd`)

## 2.6.2 XA\_API\_CMD\_GET\_LIB\_ID\_STRINGS

Table 2-10 XA\_CMD\_TYPE\_LIB\_NAME subcommand

Subcommand	XA_CMD_TYPE_LIB_NAME
Description	This subcommand obtains the name of the library in the form of a string. The maximum length of the string that the library will provide is 30 bytes. Therefore the application shall pass a pointer to a buffer of a minimum size of 30 bytes. This command is optional.
Actual Parameters	<p>p_xa_module_obj  <b>NULL</b></p> <p>i_cmd  XA_API_CMD_GET_LIB_ID_STRINGS</p> <p>i_idx  XA_CMD_TYPE_LIB_NAME</p> <p>pv_value  process name - Pointer to a character buffer in which the name of the library is returned</p>
Restrictions	None

---

**Note** No codec object is required due to the name being static data in the codec library.

---

### Example

```
char process_name[30];
res = (*api_func)(NULL,
    XA_API_CMD_GET_LIB_ID_STRINGS,
    XA_CMD_TYPE_LIB_NAME,
    (pVOID) process_name);
```

### Errors

- XA\_API\_FATAL\_MEM\_ALLOC  
This error is suppressed as p\_xa\_module\_obj is NULL
- XA\_API\_FATAL\_MEM\_ALLOC  
pv\_value is NULL

Table 2-11 XA\_CMD\_TYPE\_LIB\_VERSION subcommand

Subcommand	XA_CMD_TYPE_LIB_VERSION
Description	This subcommand obtains the version of the library in the form of a string. The maximum length of the string that the library will provide is 30 bytes. Therefore the application shall pass a pointer to a buffer of a minimum size of 30 bytes. This command is optional.
Actual Parameters	<p>p_xa_module_obj  <b>NULL</b></p> <p>i_cmd            XA_API_CMD_GET_LIB_ID_STRINGS</p> <p>i_idx            XA_CMD_TYPE_LIB_VERSION</p> <p>pv_value            lib_version – Pointer to a character buffer in which the version of the library is returned</p>
Restrictions	None

---

**Note** No codec object is required due to the version being static data in the codec library.

---

### Example

```
char lib_version[30];
res = (*api_func)(NULL,
    XA_API_CMD_GET_LIB_ID_STRINGS,
    XA_CMD_TYPE_LIB_VERSION,
    (pVOID) lib_version);
```

### Errors

- XA\_API\_FATAL\_MEM\_ALLOC  
 This error is suppressed as p\_xa\_module\_obj is NULL
- XA\_API\_FATAL\_MEM\_ALLOC  
 pv\_value is NULL

Table 2-12 XA\_CMD\_TYPE\_API\_VERSION subcommand

Subcommand	XA_CMD_TYPE_API_VERSION
Description	This subcommand obtains the version of the API in the form of a string. The maximum length of the string that the library will provide is 30 bytes. Therefore the application shall pass a pointer to a buffer of a minimum size of 30 bytes. This command is optional.
Actual Parameters	<p>p_xa_module_obj  <b>NULL</b></p> <p>i_cmd  XA_API_CMD_GET_LIB_ID_STRINGS</p> <p>i_idx  XA_CMD_TYPE_API_VERSION</p> <p>pv_value  api_version - Pointer to a character buffer in which the version of the API is returned</p>
Restrictions	None

---

**Note** No codec object is required due to the version being static data in the codec library.

---

### Example

```
char api_version[30];
res = (*api_func)(NULL,
    XA_API_CMD_GET_LIB_ID_STRINGS,
    XA_CMD_TYPE_API_VERSION,
    (pVOID) api_version);
```

### Errors

- XA\_API\_FATAL\_MEM\_ALLOC  
This error is suppressed as p\_xa\_module\_obj is NULL
- XA\_API\_FATAL\_MEM\_ALLOC  
pv\_value is NULL

## 2.6.3 XA\_API\_CMD\_GET\_API\_SIZE

Table 2-13 XA\_API\_CMD\_GET\_API\_SIZE command

Subcommand	None
Description	This command obtains the size of the API structure, in order to allocate memory for the API structure. The pointer to the API size variable is passed and the API returns the size of the structure in bytes. The API structure is used for the interface and is persistent.
Actual Parameters	<p>p_xa_module_obj  <b>NULL</b></p> <p>i_cmd  XA_API_CMD_GET_API_SIZE</p> <p>i_idx  <b>NULL</b></p> <p>pv_value  &amp;api_size - Pointer to the API size variable</p>
Restrictions	The application will allocate memory with an alignment of 4 bytes.

---

**Note** No codec object is required due to the size being fixed for the codec library.

---

### Example

```
unsigned int api_size;
res = (*api_func)(NULL,
                 XA_API_CMD_GET_API_SIZE,
                 0,
                 (pVOID) &api_size);
```

### Errors

- XA\_API\_FATAL\_MEM\_ALLOC  
This error is suppressed as p\_xa\_module\_obj is NULL
- XA\_API\_FATAL\_MEM\_ALLOC  
pv\_value is NULL

## 2.6.4 XA\_API\_CMD\_INIT

Table 2-14 XA\_CMD\_TYPE\_INIT\_API\_PRE\_CONFIG\_PARAMS subcommand

Subcommand	XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS
Description	This subcommand sets the default value of the configuration parameters. The configuration parameters can then be altered by using one of the codec-specific parameter setting commands. Refer to the codec-specific section.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_INIT</p> <p>i_idx XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS</p> <p>pv_value <b>NULL</b></p>
Restrictions	None

### Example

```
res = (*api_func)(api_obj,
                XA_API_CMD_INIT,
                XA_CMD_TYPE_INIT_API_PRE_CONFIG_PARAMS,
                NULL);
```

### Errors

- Common API Errors

Table 2-15 XA\_CMD\_TYPE\_INIT\_API\_POST\_CONFIG\_PARAMS subcommand

Subcommand	XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS
Description	This subcommand is used to calculate the sizes of all the memory blocks required by the application. It should occur after the codec-specific parameters have been set.
Actual Parameters	<p>p_xa_module_obj  api_obj - Pointer to API Structure</p> <p>i_cmd  XA_API_CMD_INIT</p> <p>i_idx  XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS</p> <p>pv_value  <b>NULL</b></p>
Restrictions	None

### Example

```
res = (*api_func)(api_obj,
                XA_API_CMD_INIT,
                XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS,
                NULL);
```

### Errors

- Common API Errors

Table 2-16 XA\_CMD\_TYPE\_INIT\_PROCESS subcommand

Subcommand	XA_CMD_TYPE_INIT_PROCESS
Description	This subcommand initializes the codec. In the case of a decoder, it searches for the valid header and performs the header decoding to get the encoded stream parameters. This command is part of the initialization loop. It must be repeatedly called until the codec signals it has finished. In the case of an encoder, the initialization of codec is performed. No output data is created during initialization.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_INIT</p> <p>i_idx XA_CMD_TYPE_INIT_PROCESS</p> <p>pv_value <b>NULL</b></p>
Restrictions	None

## Example

```
res = (*api_func)(api_obj,
                XA_API_CMD_INIT,
                XA_CMD_TYPE_INIT_PROCESS,
                NULL);
```

## Errors

- Common API Errors
- See the codec-specific section for execution errors

Table 2-17 XA\_CMD\_TYPE\_INIT\_DONE\_QUERY subcommand

Subcommand	XA_CMD_TYPE_INIT_DONE_QUERY
Description	This subcommand checks to see if the initialization process has completed. If it has, the flag value is set to 1; otherwise it is set to 0. A pointer to the flag variable is passed as an argument.
Actual Parameters	<p>p_xa_module_obj  api_obj - Pointer to API Structure</p> <p>i_cmd  XA_API_CMD_INIT</p> <p>i_idx  XA_CMD_TYPE_INIT_DONE_QUERY</p> <p>pv_value  &amp;init_done - Pointer to a flag that indicates the completion of initialization process</p>
Restrictions	None

### Example

```

unsigned int init_done;
res = (*api_func)(api_obj,
                 XA_API_CMD_INIT,
                 XA_CMD_TYPE_INIT_DONE_QUERY,
                 (pVOID) &init_done);

```

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC

pv\_value is NULL

## 2.6.5 XA\_API\_CMD\_GET\_MEMTABS\_SIZE

Table 2-18 XA\_API\_CMD\_GET\_MEMTABS\_SIZE command

Subcommand	None
Description	This command obtains the size of the table used to hold the memory blocks required for the codec operation. The API returns the total size of the required table. A pointer to the size variable is sent with this API command and the codec writes the value to the variable.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_GET_MEMTABS_SIZE</p> <p>i_idx <b>NULL</b></p> <p>pv_value &amp;proc_mem_tabs_size - Pointer to the memory table size variable</p>
Restrictions	The application shall allocate memory with an alignment of 4 bytes.

### Example

```
unsigned int proc_mem_tabs_size;
res = (*api_func)(api_obj,
                 XA_API_CMD_GET_MEMTABS_SIZE,
                 0,
                 (pVOID) &proc_mem_tabs_size);
```

### Errors

- Common API Errors
  - XA\_API\_FATAL\_MEM\_ALLOC
- pv\_value is NULL

## 2.6.6 XA\_API\_CMD\_SET\_MEMTABS\_PTR

Table 2-19 XA\_API\_CMD\_SET\_MEMTABS\_PTR command

Subcommand	None
Description	This command sets the memory structure pointer in the library to the allocated value.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_SET_MEMTABS_PTR</p> <p>i_idx <b>NULL</b></p> <p>pv_value alloc – Pointer to memory table structure.</p>
Restrictions	The application will allocate memory with an alignment of 4 bytes.

### Example

```
int * alloc; //alloc is a pointer to the allocated memory
res = (*api_func)(api_obj,
               XA_API_CMD_SET_MEMTABS_PTR,
               0,
               (pVOID) alloc);
```

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC  
pv\_value is NULL
- XA\_API\_FATAL\_MEM\_ALIGN  
pv\_value is not aligned to 4 bytes

## 2.6.7 XA\_API\_CMD\_GET\_N\_MEMTABS

Table 2-20 XA\_API\_CMD\_GET\_N\_MEMTABS command

Subcommand	None
Description	This command obtains the number of memory blocks needed by the codec. This value is used as the iteration counter for the allocation of the memory blocks. A pointer to each memory block will be placed in the previously allocated memory tables. The pointer to the variable is passed to the API and the codec writes the value to this variable.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_GET_N_MEMTABS</p> <p>i_idx <b>NULL</b></p> <p>pv_value &amp;n_mems – Pointer to the memory block count variable</p>
Restrictions	None

### Example

```
int n_mems;
res = (*api_func)(api_obj,
                 XA_API_CMD_GET_N_MEMTABS,
                 0,
                 (pVOID) &n_mems);
```

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC  
pv\_value is NULL

## 2.6.8 XA\_API\_CMD\_GET\_MEM\_INFO\_SIZE

Table 2-21 XA\_API\_CMD\_GET\_MEM\_INFO\_SIZE command

Subcommand	Memory index
Description	This command obtains the size of the memory type being referred to by the index. The size in bytes is returned in the variable pointed to by the final argument. Note this is the actual size needed, not including any alignment packing space.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_GET_MEM_INFO_SIZE</p> <p>i_idx Index of the memory</p> <p>pv_value &amp;size - Pointer to the memory size variable</p>
Restrictions	None

### Example

```
int index;
unsigned int size;
res = (*api_func)(api_obj,
                 XA_API_CMD_GET_MEM_INFO_SIZE,
                 index,
                 (pVOID) &size);
```

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC  
pv\_value is NULL
- XA\_API\_FATAL\_INVALID\_CMD\_TYPE  
i\_idx is an invalid memory block number; valid block numbers obey the relation  $0 \leq i\_idx < n\_mems$  (See XA\_API\_CMD\_GET\_N\_MEMTABS)

## 2.6.9 XA\_API\_CMD\_GET\_MEM\_INFO\_ALIGNMENT

Table 2-22 XA\_API\_CMD\_GET\_MEM\_INFO\_ALIGNMENT command

Subcommand	Memory index
Description	This command gets the alignment information of the memory-type being referred to by the index. The alignment required in bytes is returned to the application.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_GET_MEM_INFO_ALIGNMENT</p> <p>i_idx Index of the memory</p> <p>pv_value &amp;alignment - Pointer to the alignment info variable</p>
Restrictions	None

### Example

```
int index;
unsigned int alignment;
res = (*api_func)(api_obj,
                 XA_API_CMD_GET_MEM_INFO_ALIGNMENT,
                 index,
                 (pVOID) &alignment);
```

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC  
pv\_value is NULL
- XA\_API\_FATAL\_INVALID\_CMD\_TYPE  
i\_idx is an invalid memory block number; valid block numbers obey the relation  $0 \leq i\_idx < n\_mems$  (See XA\_API\_CMD\_GET\_N\_MEMTABS)

## 2.6.10 XA\_API\_CMD\_GET\_MEM\_INFO\_TYPE

Table 2-23 XA\_API\_CMD\_GET\_MEM\_INFO\_TYPE command

Subcommand	Memory index
Description	This command gets the type of memory being referred to by the index.
Actual Parameters	<p>p_xa_module_obj</p> <p>api_obj - Pointer to API Structure</p> <p>i_cmd</p> <p>XA_API_CMD_GET_MEM_INFO_TYPE</p> <p>i_idx</p> <p>Index of the memory</p> <p>pv_value</p> <p>&amp;type - Pointer to the memory type variable</p>
Restrictions	None

### Example

```
int index;
unsigned int type;
res = (*api_func)(api_obj,
    XA_API_CMD_GET_MEM_INFO_TYPE,
    index,
    (pVOID) &type);
```

Table 2-24 Memory Type Indices

Type	Description
XA_MEMTYPE_PERSIST	Persistent memory
XA_MEMTYPE_SCRATCH	Scratch memory
XA_MEMTYPE_INPUT	Input Buffer
XA_MEMTYPE_OUTPUT	Output Buffer

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC  
pv\_value is NULL
- XA\_API\_FATAL\_INVALID\_CMD\_TYPE  
i\_idx is an invalid memory block number; valid block numbers obey the relation  $0 \leq i\_idx < n\_mems$  (See XA\_API\_CMD\_GET\_N\_MEMTABS)

## 2.6.11 XA\_API\_CMD\_GET\_MEM\_INFO\_PRIORITY

Table 2-25 XA\_API\_CMD\_GET\_MEM\_INFO\_PRIORITY command

Subcommand	Memory index
Description	This command gets the allocation priority of memory being referred to by the index. (The meaning of the levels is defined on a codec-specific basis. This command returns a fixed dummy value unless the codec defines it otherwise.)
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_GET_MEM_INFO_PRIORITY</p> <p>i_idx Index of the memory</p> <p>pv_value &amp;priority - Pointer to the memory priority variable</p>
Restrictions	None

### Example

```
int index;
unsigned int priority;
res = (*api_func)(api_obj,
    XA_API_CMD_GET_MEM_INFO_PRIORITY,
    index,
    (pVOID) &priority);
```

Table 2-26 Memory Priorities

Priority	Type
0	XA_MEMPRIORITY_ANYWHERE
1	XA_MEMPRIORITY_LOWEST
2	XA_MEMPRIORITY_LOW
3	XA_MEMPRIORITY_NORM
4	XA_MEMPRIORITY_ABOVE_NORM
5	XA_MEMPRIORITY_HIGH
6	XA_MEMPRIORITY_HIGHER
7	XA_MEMPRIORITY_CRITICAL

## Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC  
`pv_value` is NULL
- XA\_API\_FATAL\_INVALID\_CMD\_TYPE  
`i_idx` is an invalid memory block number; valid block numbers obey the relation  $0 \leq i\_idx < n\_mems$  (See XA\_API\_CMD\_GET\_N\_MEMTABS)

## 2.6.12 XA\_API\_CMD\_SET\_MEM\_PTR

Table 2-27 XA\_API\_CMD\_SET\_MEM\_PTR Command

Subcommand	Memory index
Description	This command passes to the codec the pointer to the allocated memory. This is then stored in the memory tables structure allocated earlier. For the input and output buffers, it is legitimate to execute this command during the main codec loop.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_SET_MEM_PTR</p> <p>i_idx Index of the memory</p> <p>pv_value alloc - Pointer to the memory buffer allocated</p>
Restrictions	The pointer must be correctly aligned to the requirements.

### Example

```
int index;
void * alloc; //alloc is a pointer to the aligned memory
res = (*api_func)(api_obj,
    XA_API_CMD_SET_MEM_PTR,
    index,
    (pVOID) alloc);
```

## Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC  
`pv_value` is NULL
- XA\_API\_FATAL\_INVALID\_CMD\_TYPE  
`i_idx` is an invalid memory block number; valid block numbers obey the relation  $0 \leq i\_idx < n\_mems$  (See XA\_API\_CMD\_GET\_N\_MEMTABS)
- XA\_API\_FATAL\_MEM\_ALIGN  
`pv_value` is not of the required alignment for the requested memory block

## 2.6.13 XA\_API\_CMD\_INPUT\_OVER

Table 2-28 XA\_API\_CMD\_INPUT\_OVER command

Subcommand	None
Description	This command tells the codec that the end of the input data has been reached. This situation can arise both in the initialization loop and the execute loop.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_INPUT_OVER</p> <p>i_idx <b>NULL</b></p> <p>pv_value <b>NULL</b></p>
Restrictions	None

### Example

```
res = (*api_func)(api_obj,
                XA_API_CMD_INPUT_OVER,
                0,
                NULL);
```

### Errors

- Common API Errors

## 2.6.14 XA\_API\_CMD\_SET\_INPUT\_BYTES

Table 2-29 XA\_API\_CMD\_SET\_INPUT\_BYTES command

Subcommand	None
Description	This command sets the number of bytes available in the input buffer for the codec. It is used both in the initialization loop and execute loop. It is the number of valid bytes from the buffer pointer. It should be at least the minimum buffer size requested unless this is the end of the data.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_SET_INPUT_BYTES</p> <p>i_idx <b>NULL</b></p> <p>pv_value &amp;buff_size - Pointer to the input buffer size variable</p>
Restrictions	None

### Example

```
int buff_size;
res = (*api_func)(api_obj,
                XA_API_CMD_SET_INPUT_BYTES,
                0,
                (pVOID) &buff_size);
```

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC
  - pv\_value is NULL

## 2.6.15 XA\_API\_CMD\_GET\_CURIDX\_INPUT\_BUF

Table 2-30 XA\_API\_CMD\_GET\_CURIDX\_INPUT\_BUF command

Subcommand	None
Description	This command gets the number of input buffer bytes consumed by the codec. It is used both in the initialization loop and execute loop.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_GET_CURIDX_INPUT_BUF</p> <p>i_idx <b>NULL</b></p> <p>pv_value &amp;bytes_consumed - Pointer to the bytes consumed variable</p>
Restrictions	None

### Example

```
int bytes_consumed;
res = (*api_func)(api_obj,
                XA_API_CMD_GET_CURIDX_INPUT_BUF,
                0,
                (pVOID) &bytes_consumed);
```

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC

pv\_value is NULL

## 2.6.16 XA\_API\_CMD\_EXECUTE

Table 2-31 XA\_CMD\_TYPE\_DO\_EXECUTE subcommand

Subcommand	XA_CMD_TYPE_DO_EXECUTE
Description	This command executes the codec.
Actual Parameters	<p>p_xa_module_obj  api_obj - Pointer to API Structure</p> <p>i_cmd  XA_API_CMD_EXECUTE</p> <p>i_idx  XA_CMD_TYPE_DO_EXECUTE</p> <p>pv_value  <b>NULL</b></p>
Restrictions	None

### Example

```
res = (*api_func)(api_obj,
                XA_API_CMD_EXECUTE,
                XA_CMD_TYPE_DO_EXECUTE,
                NULL);
```

### Errors

- Common API Errors
- See the codec-specific section for execution errors

Table 2-32 XA\_CMD\_TYPE\_DONE\_QUERY subcommand

Subcommand	XA_CMD_TYPE_DONE_QUERY
Description	This command checks to see if the end of processing has been reached. If it has, the flag value is set to 1; otherwise it is set to 0. The pointer to the flag is passed as an argument. Processing by the codec can continue for several invocations of the DO_EXECUTE command after the last input data has been passed to the codec, thus the application should not assume that the codec has finished generating all its output until so indicated by this command.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_EXECUTE</p> <p>i_idx XA_CMD_TYPE_DONE_QUERY</p> <p>pv_value &amp;flag - Pointer to the done query flag variable</p>
Restrictions	None

## Example

```
int flag;
res = (*api_func)(api_obj,
                 XA_API_CMD_EXECUTE,
                 XA_CMD_TYPE_DONE_QUERY,
                 (pVOID) &flag);
```

## Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC

pv\_value is NULL

## 2.6.17 XA\_API\_CMD\_GET\_OUTPUT\_BYTES

Table 2-33 XA\_API\_CMD\_GET\_OUTPUT\_BYTES command

Subcommand	None
Description	This command obtains the number of bytes output by the codec during the last execution.
Actual Parameters	<p>p_xa_module_obj api_obj - Pointer to API Structure</p> <p>i_cmd XA_API_CMD_GET_OUTPUT_BYTES</p> <p>i_idx <b>NULL</b></p> <p>pv_value &amp;out_bytes - Pointer to the output bytes variable</p>
Restrictions	None

### Example

```
int out_bytes;
res = (*api_func)(api_obj,
    XA_API_CMD_GET_OUTPUT_BYTES,
    0,
    (pVOID) &out_bytes);
```

### Errors

- Common API Errors
- XA\_API\_FATAL\_MEM\_ALLOC

pv\_value is NULL

### 3. HiFi Audio Codec API Specifics

The flow chart of a typical API command sequence is provided below.




Figure 3 Flow Chart for Typical Command Sequence

A HiFi Audio Codec must conform to the generic codec API. However, it can have optional codec-specific additions.

Section 3.1 shows the files and details of API calls that may be specific to a particular codec. Section 3.2 describes codec specific error codes. Configuration parameters, usage notes, and codec specific commands are described in Section 3.3.

## ***3.1 Codec Specific Files***

The codec API is required to be delivered in the form of a single header file (typically called `xa_<codec>_api.h`) and a single library file (typically called `xa_<codec>.a`). The library would be built using a specific version of the Xtensa tools on a specific core. As described in Table 2-1, the library will expose a single entry point.

## ***3.2 Codec Specific Error Codes***

Other than common error codes explained in Section 2, the codec may also report error codes specific to itself. These could be fatal or non-fatal errors.

## ***3.3 Configuration Parameters***

The codec may allow the application to write or read codec parameters using the SET CONFIG API (see Section 3.3.1). Similarly, the application can read codec parameters using the GET CONFIG API (see Section 3.3.2).

### 3.3.1 XA\_API\_CMD\_SET\_CONFIG\_PARAM

The table below provides the generic format to set a codec parameter, denoted by XXX.

Table 3-1 XA\_API\_CMD\_SET\_CONFIG\_PARAM

Subcommand	XA_<CODEC>_CONFIG_PARAM_XXX
Description	Sets the codec parameter XXX. Some of the codec parameters may have a default value and need not set explicitly.
Actual Parameters	p_xa_module_obj api_obj - Pointer to API Structure  i_cmd XA_API_CMD_SET_CONFIG_PARAM  i_idx XA_<CODEC>_CONFIG_PARAM_XXX  pv_value &value: Pointer to the parameter variable.
Restrictions	The codec may impose restrictions on when a particular parameter can be set. For example, a particular parameter may have an impact on the amount of memory that is required. Such a parameter would need to be set before the call to XA_CMD_TYPE_INIT_API_POST_CONFIG_PARAMS

#### Example

Example to set the sampling rate for the hypothetical encoder `GENERIC_ENC`:

```
int sample_rate = 48000;
res = (*api_func)(api_obj,
                 XA_API_CMD_SET_CONFIG_PARAM,
                 XA_GENERIC_ENC_CONFIG_PARAM_SAMPLE_RATE,
                 (pVOID) &sample_rate);
```

Here XXX is 'SAMPLE\_RATE'.

#### Errors

- Common API Errors
- Possible codec-specific API Errors

### 3.3.2 XA\_API\_CMD\_GET\_CONFIG\_PARAM

The table below provides the generic format to get the value of codec parameter, denoted by XXX.

Table 3-2 XA\_API\_CMD\_GET\_CONFIG\_PARAM

Subcommand	XA_<CODEC>_CONFIG_PARAM_XXX
Description	Gets the value of codec parameter XXX. Reading a codec parameter before it is explicitly set returns the default value.
Actual Parameters	p_xa_module_obj api_obj - Pointer to API Structure  i_cmd XA_API_CMD_GET_CONFIG_PARAM  i_idx XA_<CODEC>_CONFIG_PARAM_XXX  pv_value & value: Pointer to the parameter variable.
Restrictions	The codec may impose restrictions on when a particular parameter can be read. For example, a particular parameter may be valid only after the first frame is processed. Such a parameter would need to be read after the first successful call to XA_CMD_TYPE_EXEC_PROCESS.

#### Example

Example to read the sampling rate for the hypothetical encoder GENERIC\_ENC:

```
int sample_rate;
res = (*api_func)(api_obj,
    XA_API_CMD_GET_CONFIG_PARAM,
    XA_GENERIC_ENC_CONFIG_PARAM_SAMPLE_RATE,
    (pVOID) &sample_rate);
Here XXX is 'SAMPLE_RATE'.
```

#### Errors

- Common API Errors
- Possible codec-specific API Errors

### 3.3.3 Configuration Parameter Details

The Programmer's Guide for a specific codec describes the parameters that are supported by the `XA_API_CMD_SET_CONFIG_PARAM` and `XA_API_CMD_GET_CONFIG_PARAM` functions described above.

The following information is typically included:

- Sub-command: Index that identifies the parameter (`i_idx`).
- Description: Describes the parameter.
- RW: Indicates if the parameter can be read (`GET`) and/or written (`SET`).
- Value type: A pointer (`pv_value`) to a variable of this type is to be passed.
- Range: Allowed values for the parameter.
- Default: Default value of the parameter. This is the value of the parameter, if you do not change or set it.

## 4. References

---

- [1] Xtensa® Software Development Toolkit User's Guide.  
*<TOOLS\_PATH>\XtDevTools\downloads\<TOOLS\_VERSION>\docs\sw\_dev\_toolkit\_ug.pdf*
  
- [2] HiFi Audio Engine User's Guide  
*<TOOLS\_PATH>\XtDevTools\downloads\<TOOLS\_VERSION>\docs\HiFi\*\_ug.pdf*
  
- [3] HiFi Speech Codec API Definition  
*HiFi-Speech-Codec-API-Definition.docx, available in the same directory.*